

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
  - **Trade name:** YACHTCARE EPOXY PRIMER 2-K (Basis)
  - **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
  - **Application of the substance / the mixture**  
Epoxy coating  
Epoxy resin
  - **1.3 Details of the supplier of the safety data sheet**
  - **Manufacturer/Supplier:**  
Vosschemie GmbH  
Esinger Steinweg 50  
D-25436 Uetersen  
Phone: +49 (0)4122 717 0; Fax: +49 (0)4122 717158; info@vosschemie.de
  - **Further information obtainable from:**  
Abteilung Labor / +49 (0)4122 717 0  
s.schaller@vosschemie.de
  - **1.4 Emergency telephone number:**  
Giftinformationszentrum (GIZ)-Nord, Goettingen, Deutschland  
Phone: +49 (0)551 19240
- 

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3

H226

Flammable liquid and vapour.

(Contd. on page 2)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)

(Contd. of page 1)



GHS05 corrosion

Eye Dam. 1      H318      Causes serious eye damage.



GHS07

Skin Irrit. 2      H315      Causes skin irritation.

Skin Sens. 1      H317      May cause an allergic skin reaction.

STOT SE 3      H335-H336      May cause respiratory irritation. May cause drowsiness or dizziness.

Aquatic Chronic 3      H412      Harmful to aquatic life with long lasting effects.

## · 2.2 Label elements

## · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

## · Hazard pictograms



GHS02



GHS05



GHS07

## · Signal word Danger

## · Hazard-determining components of labelling:

butan-1-ol

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $700 \leq 1200$ )  
Solvent naphtha (petroleum), light arom.

## · Hazard statements

H226      Flammable liquid and vapour.

H315      Causes skin irritation.

H318      Causes serious eye damage.

H317      May cause an allergic skin reaction.

H335-H336      May cause respiratory irritation. May cause drowsiness or dizziness.

H412      Harmful to aquatic life with long lasting effects.

## · Precautionary statements

P101      If medical advice is needed, have product container or label at hand.

P102      Keep out of reach of children.

P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280      Wear protective gloves/protective clothing/eye protection/face protection.

P261      Avoid breathing mist/vapours/spray.

P273      Avoid release to the environment.

P264      Wash thoroughly after handling.

P303+P361+P353      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338      IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310      Immediately call a POISON CENTER/doctor.

P304+P340      IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

(Contd. of page 2)

P403+P235 Store in a well-ventilated place. Keep cool.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**  
Contains epoxy constituents. May produce an allergic reaction.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $700 \leq 1200$ ) ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	10-<25%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	10-<25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene, mixture of isomers ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-<20%
CAS: 71-36-3 EINECS: 200-751-6 Reg.nr.: 01-2119484630-38	butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	5.0-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	1.0-<3.0%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Personal protection for the First Aider.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Remove person to fresh air and keep comfortable for breathing.

In case of unconsciousness place patient stably in side position for transportation.

Call a POISON CENTER/doctor if you feel unwell.

· **After skin contact:**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash with plenty of soap and water.

Use skin protection cream for skin protection.

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

(Contd. of page 3)

If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a doctor immediately.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

· **Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Ensure adequate ventilation

Keep away from ignition sources.

· **6.2 Environmental precautions:**

Avoid release to the environment.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

Collect with an inert, non-combustible, absorbent material (i.e. sand, diatomaceous earth, acid binder, universal binder).

Dispose contaminated material as waste according to item 13.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

See Section 13 for disposal information.

(Contd. of page 4)

**SECTION 7: Handling and storage**

**· 7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

**· Information about fire - and explosion protection:**

Vapours of the product are heavier than air and may accumulate on the ground, in mines, drains or cellars with high concentration.

Fumes can combine with air to form an explosive mixture.

Use explosion-proof apparatus / fittings and spark-proof tools.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Ground/bond container and receiving equipment.

**· 7.2 Conditions for safe storage, including any incompatibilities**

**· Storage:**

**· Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Adhere to the provisions of the Law on Water Protection.

**· Information about storage in one common storage facility:**

Store away from oxidising agents.

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

Keep away from foodstuffs, beverages and feed.

**· Further information about storage conditions:**

Store under lock and key and with access restricted to technical experts or their assistants only.

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Keep ignition sources away - Do not smoke.

Anti-explosion protection required

**· 7.3 Specific end use(s) No further relevant information available.**

**SECTION 8: Exposure controls/personal protection**

**· Additional information about design of technical facilities:** No further data; see item 7.

**· 8.1 Control parameters**

**· Ingredients with limit values that require monitoring at the workplace:**

**64742-95-6 Solvent naphtha (petroleum), light arom.**

OEL (EU)

Long-term value: 120 mg/m<sup>3</sup>, 25 ppm

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

(Contd. of page 5)

**1330-20-7 xylene, mixture of isomers**

WEL (Great Britain)	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
IOELV (EU)	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm Skin

**71-36-3 butan-1-ol**

WEL (Great Britain)	Short-term value: 154 mg/m <sup>3</sup> , 50 ppm Sk
---------------------	--

**100-41-4 ethylbenzene**

WEL (Great Britain)	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
IOELV (EU)	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm Long-term value: 442 mg/m <sup>3</sup> , 100 ppm Skin

**· DNELs**

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	Long-term exposure - systemic effects	11 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	11 mg/kg bw/day (general population) 25 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	32 mg/m <sup>3</sup> (general population) 150 mg/m <sup>3</sup> (worker)

**1330-20-7 xylene, mixture of isomers**

Oral	Long-term exposure - systemic effects	1.6 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	108 mg/kg bw/day (general population) 180 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	14.8 mg/m <sup>3</sup> (general population) 77 mg/m <sup>3</sup> (worker)
	Acute/short-term exposure - systemic effects	174 mg/m <sup>3</sup> (general population) 289 mg/m <sup>3</sup> (worker)
	Acute/short-term exposure - local effects	174 mg/m <sup>3</sup> (general population) 289 mg/m <sup>3</sup> (worker)

**100-41-4 ethylbenzene**

Oral	Long-term exposure - systemic effects	1.6 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	180 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	15 mg/m <sup>3</sup> (general population) 77 mg/m <sup>3</sup> (worker)
	Acute/short-term exposure - local effects	293 mg/m <sup>3</sup> (worker)

**· PNECs**

**1330-20-7 xylene, mixture of isomers**

PNEC aqua	0.327 mg/l (freshwater)
-----------	-------------------------

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

(Contd. of page 6)

PNEC sediment	0.327 mg/l (marine water)
	0.327 mg/l (intermittent releases)
	12.46 mg/kg (freshwater)
	12.46 mg/kg (marine water)

**100-41-4 ethylbenzene**

PNEC aqua	0.1 mg/l (freshwater)
	0.01 mg/l (marine water)
	0.1 mg/l (intermittent releases)
PNEC sediment	13.7 mg/kg (freshwater)
	2.68 mg/kg (marine water)
PNEC STP	9.6 mg/l
PNEC soil	2.68 mg/kg (soil dw)
PNEC oral	0.02 mg/kg

**· Ingredients with biological limit values:**

**1330-20-7 xylene, mixture of isomers**

BMGV (Great Britain)	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Immediately remove all soiled and contaminated clothing

Wash contaminated clothing before reuse.

Contaminated work clothing should not be allowed out of the workplace.

Avoid contact with the eyes and skin.

Use skin protection cream for skin protection.

· **Respiratory protection:**

Adhere to the workplace limit values and / or other threshold values.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

(Contd. of page 7)

Check the permeability prior to each renewed use of the glove.  
Preventive skin protection by use of skin-protecting agents is recommended.

· **Material of gloves**

Fluorocarbon rubber (Viton)

Recommended thickness of the material:  $\geq 0.7$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Value for the permeation: Level  $\leq 6$  ( $\geq 480$  min.)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Not suitable are gloves made of the following materials:**

Nitrile rubber, NBR

Butyl rubber, BR

Natural rubber, NR

Neoprene gloves

PVC gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Liquid

**Colour:** Coloured

· **Odour:** Solvent-like

· **pH-value:** Not determined

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** Undetermined.

· **Flash point:** 31 °C

· **Ignition temperature:** Not determined

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

**Lower:** 0.8 Vol %

**Upper:** 11.3 Vol %

· **Vapour pressure:** Not determined.

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)

(Contd. of page 8)

· <b>Density at 20 °C:</b>	1.4 g/cm <sup>3</sup>
· <b>Vapour density</b>	Not determined
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No decomposition if used according to specifications.
- **10.2 Chemical stability** No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**  
Reacts with oxidising agents.  
Reacts with reducing agents.
- **10.4 Conditions to avoid**  
Protect from heat.  
Avoid naked flames, sparks, other ignition sources and sunlight.
- **10.5 Incompatible materials:**  
Reacts with oxidising agents.  
Reacts with reducing agents.
- **10.6 Hazardous decomposition products:**  
Formation of toxic gases is possible during heating or in case of fire.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

Oral	ATE	10730.4 mg/kg (mix) (Calculation method)
Dermal	ATE	10795.9 mg/kg (mix) (Calculation method)
Inhalative	ATE	88.53 mg/l (mix) (4h / vapours ; Calculation method)

**25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight 700 ≤ 1200)**

Oral	LD50	> 5000 mg/kg (rat)
Dermal	LD50	> 2000 mg/kg (rabbit)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD 50	> 6800 mg/kg (rat)
Dermal	LD 50	> 3400 mg/kg (rabbit)
Inhalative	LC 50 / 4h	> 10.2 mg/l (rat)

**1330-20-7 xylene, mixture of isomers**

Oral	LD 50	> 4000 mg/kg (rat)
------	-------	--------------------

(Contd. on page 10)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

(Contd. of page 9)

Dermal	LD 50	> 1700 mg/kg (rabbit)
Inhalative	LC 50 / 4h	21.7 mg/l (rat) (Vapour)
	LC50 /4h	6350 ppm (rat) (vapour)
<b>71-36-3 butan-1-ol</b>		
Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3400 mg/kg (rabbit)
Inhalative	LC50 /4h	25 mg/m <sup>3</sup> (rat)
<b>100-41-4 ethylbenzene</b>		
Oral	LD50	3500 mg/kg (rat)
Dermal	LD 50	> 5000 mg/kg (rabbit)
Inhalative	LC50 /4h	17.2 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Additional toxicological information:** May cause respiratory irritation.
- **Sensitisation**  
Sensitisation possible through skin contact.  
Contains reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight 700 ≤ 1200). May produce an allergic reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**  
No further relevant information available.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### · 12.1 Toxicity

#### · Aquatic toxicity:

#### **64742-95-6 Solvent naphtha (petroleum), light arom.**

EC50/48h	6.14 mg/l (daphnia magna)
EL50/72h	56 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
LC50/96h	9.22 mg/l (oncorhynchus mykiss)
LL50/96h	10 mg/l (oncorhynchus mykiss) (OECD 203)
NOELR (aqua chron.)	2.6 mg/l (daphnia magna) (OECD 211, 21d)
	2.6 mg/l (pimephales promelas) (OECD 204, 14d)

#### **1330-20-7 xylene, mixture of isomers**

EC50	> 175 mg/l (activated slugde)
EC50/48h	3.82 mg/l (daphnia magna)

(Contd. on page 11)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

(Contd. of page 10)

EC50/72h	8.5 mg/l ( <i>palaemonetes pugio</i> ) (marine water)
LC50/96h	4.7 mg/l ( <i>Pseudokirchneriella subcapitata</i> )
	> 780 mg/l ( <i>Cyprinus carpio</i> )
	13.1 - 16.5 mg/l ( <i>Lepomis macrochirus</i> )
	7.6 mg/l ( <i>oncorhynchus mykiss</i> )
	13.4 mg/l ( <i>pimephales promelas</i> )
NOEC	> 1.3 mg/l ( <i>oncorhynchus mykiss</i> ) (56 d)

**71-36-3 butan-1-ol**

EC50/48h	1983 mg/l ( <i>daphnia magna</i> )
EC50/72h	> 500 mg/l ( <i>Pseudokirchneriella subcapitata</i> )
LC50/96h	1730 mg/l ( <i>pimephales promelas</i> )

**100-41-4 ethylbenzene**

EC50/48h	2.4 mg/l ( <i>daphnia magna</i> )
	> 5.2 mg/l ( <i>americamysis bahia</i> )
EC50/72h	4.6 mg/l ( <i>Pseudokirchneriella subcapitata</i> )
LC50/96h	4.2 mg/l ( <i>oncorhynchus mykiss</i> )

**· 12.2 Persistence and degradability**

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Biodegradation	74.3 % (ISO/DIS 14593, 28d)
----------------	-----------------------------

**1330-20-7 xylene, mixture of isomers**

Biodegradation	87.8 % (28d)
----------------	--------------

**71-36-3 butan-1-ol**

Biodegradation	92 % (20d)
----------------	------------

**100-41-4 ethylbenzene**

Biodegradation	> 70 % (28 d)
----------------	---------------

**· 12.3 Bioaccumulative potential**

**64742-95-6 Solvent naphtha (petroleum), light arom.**

log Kow	> 3
BCF	10 - 2500 (lit.) (calculated)

**1330-20-7 xylene, mixture of isomers**

log Pow	> 3
BCF	6 - 23.4 ( <i>oncorhynchus mykiss</i> )

**71-36-3 butan-1-ol**

log Pow	1
BCF	3.16

**100-41-4 ethylbenzene**

log Pow	3.1
---------	-----

**· Behaviour in environmental systems:**

**· 12.4 Mobility in soil**

**64742-95-6 Solvent naphtha (petroleum), light arom.**

log Koc	1.783 - 2.36 (lit.) (calculated value)
Koc	60.7 - 229.2 (lit.) (calculated value)

(Contd. on page 12)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

(Contd. of page 11)

- **Additional ecological information:**
- **General notes:**  
Very toxic for aquatic organisms  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste disposal key:**  
The waste codes given above are to be considered recommendations; because of regional and industrial sector specific features, application of different waste codes is possible.

· **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances
15 01 10*	packaging containing residues of or contaminated by dangerous substances

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1263

- **14.2 UN proper shipping name**
- **ADR** 1263 PAINT
- **IMDG, IATA** PAINT

- **14.3 Transport hazard class(es)**

- **ADR, IMDG, IATA**



- **Class** 3 Flammable liquids.
- **Label** 3

- **14.4 Packing group**
- **ADR, IMDG, IATA** III

- **14.5 Environmental hazards:** Product contains environmentally hazardous substances: zinc oxide, Solvent naphtha (petroleum), light arom.

- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Danger code (Kemler):** 30

(Contd. on page 13)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

(Contd. of page 12)

- |  |                 |
|--|-----------------|
| · <b>EMS Number:</b>   | <u>F-E,S-E</u>  |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b> | Not applicable. |
| · <b>Transport/Additional information:</b>                                       |                 |
| · <b>ADR</b>   |                 |
| · <b>Limited quantities (LQ)</b>   | 5L              |
| · <b>Transport category</b>  | 3               |
| · <b>Tunnel restriction code</b>   | D/E             |

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Information about limitation of use:**  
Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.
- **Classification according to Regulation (EC) No 1272/2008**
- Flam. Liq.3, H226
- Eye Dam.1, H318
- Skin. Irrit.2, H315
- Skin. Sens.1, H317
- Classification procedure**  
Bridging principle "Substantially similar mixtures"  
Calculation method  
Calculation method  
Calculation method

(Contd. on page 14)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 17.11.2016

V - 2

Revision: 17.11.2016

**Trade name: YACHTCARE EPOXY PRIMER 2-K (Basis)**

(Contd. of page 13)

STOT SE 3,H335

Calculation method

STOT SE 3,H336

Calculation method

Aquatic Chronic 3,H412

Calculation method

· **Department issuing SDS:** Abteilung Labor

· **Contact:** Frau S. Schaller

· **Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ICAO: International Civil Aviation Organisation*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*DNEL: Derived No-Effect Level (REACH)*

*PNEC: Predicted No-Effect Concentration (REACH)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Flam. Liq. 2: Flammable liquids – Category 2*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Irrit. 2: Skin corrosion/irritation – Category 2*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*

*Skin Sens. 1: Skin sensitisation – Category 1*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

*Asp. Tox. 1: Aspiration hazard – Category 1*

*Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

· **\* Data compared to the previous version altered.**

GB