

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
 - **Trade name:** YACHTCARE EPOXY FIBER FILLER (B-Komponente)
 - **1.2 Relevant identified uses of the substance or mixture and uses advised against** Not determined
 - **Application of the substance / the mixture**
Hardening agent/ Curing agent
Epoxy curing agent
Knife filler/ Surfacer
 - **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
Vosschemie GmbH
Esinger Steinweg 50
D-25436 Uetersen
Phone: +49 (0)4122 717 0; Fax: +49 (0)4122 717158; info@vosschemie.de
 - **Further information obtainable from:**
Abteilung Labor / +49 (0)4122 717 0
s.schaller@vosschemie.de
 - **1.4 Emergency telephone number:**
Giftinformationszentrum (GIZ)-Nord, Goettingen, Deutschland
Phone: +49 (0)551 19240
-

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.

(Contd. on page 2)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: YACHTCARE EPOXY FIBER FILLER (B-Komponente)

(Contd. of page 1)



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS05 GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labelling:**

m-phenylenebis(methylamine)

3-aminomethyl-3,5,5-trimethylcyclohexylamine

trimethylhexane-1,6-diamine

Fatty acids, tall-oil, compds. with oleylamine

· **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: YACHTCARE EPOXY FIBER FILLER (B-Komponente)

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	<i>m</i> -phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-<30%
CAS: 2855-13-2 EINECS: 220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	5.0-<10%
CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	5.0-<10%
CAS: 25620-58-0 EINECS: 247-134-8	trimethylhexane-1,6-diamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	1.0-<5.0%
CAS: 98-54-4 EINECS: 202-679-0	4-tert-butylphenol ⚠ Repr. 2, H361fd; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H335	1.0-<5.0%
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17	Salicylic acid ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302	1.0-<3.0%
CAS: 85711-55-3 EINECS: 288-315-1 Reg.nr.: 01-2119974148-28	Fatty acids, tall-oil, compds. with oleylamine ⚠ STOT RE 2, H373; ⚠ Eye Dam. 1, H318; ⚠ Skin Sens. 1A, H317	<0.5%
CAS: 1760-24-3 EINECS: 217-164-6	N-(3-(trimethoxysilyl)propyl)ethylenediamine ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	<0.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Immediately remove any clothing soiled by the product.

· **After inhalation:**

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

· **After eye contact:**

Rinse opened eye for several minutes under running water. Then consult a doctor.

Call a doctor immediately.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: YACHTCARE EPOXY FIBER FILLER (B-Komponente)

(Contd. of page 3)

- **After swallowing:**
 - Do not induce vomiting; call for medical help immediately.
 - Rinse out mouth and then drink plenty of water.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
 - No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
 - CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
 - Carbon monoxide (CO)
 - Nitrogen oxides (NO_x)
 - Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
 - Do not inhale explosion gases or combustion gases.
- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
 - Avoid contact with the eyes and skin.
 - Ensure adequate ventilation
 - Do not inhale gases / fumes / aerosols.
 - Keep away from ignition sources.
- **6.2 Environmental precautions:**
 - Do not allow to penetrate the ground/soil.
 - Do not allow to enter sewers/ surface or ground water.
 - Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
 - Collect with an inert, non-combustible, absorbent material (i.e. sand, diatomaceous earth, acid binder, universal binder).
 - Dispose of the material collected according to regulations.
- **6.4 Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Keep receptacles tightly sealed.
 - Open and handle receptacle with care.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: YACHTCARE EPOXY FIBER FILLER (B-Komponente)

(Contd. of page 4)

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

Prevent formation of aerosols.

Do not inhale gases / fumes / aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: Store only in the original receptacle.

· Information about storage in one common storage facility:

Keep away from foodstuffs, beverages and feed.

Do not store together with oxidising and acidic materials.

Do not store together with alkalis (caustic solutions).

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Protect from humidity and water.

Protect from frost.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

69-72-7 Salicylic acid

Oral	Acute/short-term exposure - systemic effects	4 mg/kg bw/day (general population)
	Long-term exposure - systemic effects	1 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	2 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	4 mg/m ³ (general population)
		5 mg/m ³ (worker)
	Long-term exposure - local effects	0.2 mg/m ³ (general population)

· PNECs

69-72-7 Salicylic acid

PNEC aqua	0.2 mg/l (freshwater)
	0.02 mg/l (marine water)
PNEC sediment	1.42 mg/kg (freshwater)
	0.142 mg/kg (marine water)
PNEC STP	162 mg/l

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: YACHTCARE EPOXY FIBER FILLER (B-Komponente)

(Contd. of page 5)

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Store protective clothing separately.

Immediately remove all soiled and contaminated clothing

Take off contaminated clothing.

Wash hands before breaks and at the end of work.

Use skin protection cream for skin protection.

Avoid contact with the eyes and skin.

After contact with skin, wash immediately with plenty of soap and water.

· **Respiratory protection:**

Ensure good ventilation/exhaustion at the workplace.

Adhere to the workplace limit values and / or other threshold values.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Check the permeability prior to each renewed use of the glove.

Preventive skin protection by use of skin-protecting agents is recommended.

· **Material of gloves**

DIN EN 374

Fluorocarbon rubber (Viton)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR**

· **Eye protection:**



Tightly sealed goggles

Face protection

· **Body protection: Protective work clothing**

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: YACHTCARE EPOXY FIBER FILLER (B-Komponente)

(Contd. of page 6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Pasty
Colour:	Grey
Odour:	Amine-like

· Change in condition

Initial boiling point and boiling range: Undetermined.

· Flash point: > 100 °C

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Density at 20 °C: 1.9 g/cm³

· Solubility in / Miscibility with water: Insoluble.

· Partition coefficient: n-octanol/water: Not determined

· Viscosity:

Dynamic: Not determined

Kinematic: Not determined

· 9.2 Other information: No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity: No decomposition if used and stored according to specifications.

· 10.2 Chemical stability: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions: Reacts with acids, alkalis and oxidising agents.

· 10.4 Conditions to avoid: No further relevant information available.

· 10.5 Incompatible materials: Reacts with acids, alkalis and oxidising agents.

· 10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

Nitrogen oxides (NO_x)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity

Harmful if swallowed.

· LD/LC50 values relevant for classification:

Oral	ATE	1698.50 mg/kg (Calculation in accordance with VO (EC) 1272/2008)
------	-----	------------------------------------------------------------------

1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	1040 mg/kg (rat)
------	------	------------------

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: YACHTCARE EPOXY FIBER FILLER (B-Komponente)

(Contd. of page 7)

Inhalative	LC 50 / 4h	2.4 mg/l (rat) (OECD 403, Dust)
2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Oral	LD50	1030 mg/kg (rat)
Dermal	LD50	1840 mg/kg (rabbit)
100-51-6 Benzyl alcohol		
Oral	LD 50	1230 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC 50 / 4h	> 4.178 mg/l (rat) (OECD-403 (Aerosol))
98-54-4 4-tert-butylphenol		
Oral	LD50	2951 mg/kg (rat)
Dermal	LD50	2288 mg/kg (rabbit)
69-72-7 Salicylic acid		
Oral	LD50	891 mg/kg (rat)
Dermal	LD 50	> 2000 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**
Causes serious eye damage.
- **Subacute to chronic toxicity:** No further relevant information available.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Carcinogenicity** No further relevant information available.
- **Reproductive toxicity/Fertility** No further relevant information available.
- **Reproductive toxicity/Teratogenicity** No further relevant information available.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

1477-55-0 m-phenylenebis(methylamine)

EC50/48h	15.2 mg/l (daphnia magna) (OECD 202)
EC50/72h	20.3 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50/0.5h	> 1000 mg/l (activated sludge) (OECD 209)
LC50/96h	87.6 mg/l (Oryzias latipes) (OECD 203)
NOEC	4.7 mg/l (daphnia magna) (OECD 211, 21d)

100-51-6 Benzyl alcohol

EL50/72h	700 mg/l (algae)
LC50/96h	10 mg/l (Lepomis macrochirus)

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: YACHTCARE EPOXY FIBER FILLER (B-Komponente)

(Contd. of page 8)

69-72-7 Salicylic acid

EC50	180 mg/l (daphnia) (24h)
EC50/48h	870 mg/l (daphnia magna) (OECD 202)
EC50/72h	100 mg/l (Pseudokirchneriella subcapitata)
	> 100 mg/l (desmodesmus subspicatus)
LC50/96h	1380 mg/l (pimephales promelas)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential**

100-51-6 Benzyl alcohol

log Kow	1.05
---------	------

69-72-7 Salicylic acid

log Pow	2.21
---------	------

· **Behaviour in environmental systems:**

· **12.4 Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste disposal key:**

The waste codes given above are to be considered recommendations; because of regional and industrial sector specific features, application of different waste codes is possible.

· **European waste catalogue**

16 05 06*	laboratory chemicals, consisting of or containing dangerous substances, including mixtures of laboratory chemicals
-----------	--------------------------------------------------------------------------------------------------------------------

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN2735

· **14.2 UN proper shipping name**

· **ADR**

2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: YACHTCARE EPOXY FIBER FILLER (B-Komponente)

(Contd. of page 9)

· **IMDG, IATA** AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class** 8 Corrosive substances.
· **Label** 8

· **14.4 Packing group**

· **ADR, IMDG, IATA** II

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user**

Warning: Corrosive substances.
· **Danger code (Kemler):** 80
· **EMS Number:** F-A,S-B
· **Stowage Category** A
· **Segregation Code** SG35 Stow "separated from" acids.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L
· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
· **Transport category** 2
· **Tunnel restriction code** E

· **IMDG**

· **Limited quantities (LQ)** 1L
· **Excepted quantities (EQ)** Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **National regulations:**

· **Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

(Contd. on page 11)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.05.2017

V - 2

Revision: 10.05.2017

Trade name: YACHTCARE EPOXY FIBER FILLER (B-Komponente)

(Contd. of page 10)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· **Department issuing SDS:** Abteilung Labor

· **Contact:** Frau S. Schaller

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1A: Skin sensitisation – Category 1A
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**