

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
  - **Trade name:** CHP-HÄRTER
  - **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
  - **Application of the substance / the mixture** Hardening agent/ Curing agent
  - **1.3 Details of the supplier of the safety data sheet**
  - **Manufacturer/Supplier:**  
Vosschemie GmbH  
Esinger Steinweg 50  
D-25436 Uetersen  
Phone: +49 (0)4122 717 0; Fax: +49 (0)4122 717158; info@vosschemie.de
  - **Further information obtainable from:**  
Abteilung Labor / +49 (0)4122 717 0  
s.schaller@vosschemie.de
  - **1.4 Emergency telephone number:**  
Giftinformationszentrum (GIZ)-Nord, Goettingen, Deutschland  
Phone: +49 (0)551 19240
- 

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Org. Perox. D H242 Heating may cause a fire.



GHS05 corrosion

(Contd. on page 2)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**Trade name: CHP-HÄRTER**

(Contd. of page 1)

*Skin Corr. 1B H314 Causes severe skin burns and eye damage.*

*Eye Dam. 1 H318 Causes serious eye damage.*



GHS07

*STOT SE 3 H335 May cause respiratory irritation.*

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

*The product is classified and labelled according to the CLP regulation.*

· **Hazard pictograms**



GHS02

GHS05

GHS07

· **Signal word Danger**

· **Hazard-determining components of labelling:**

*cyclohexanone, peroxide*

*4-hydroxy-4-methylpentan-2-one*

· **Hazard statements**

*H242 Heating may cause a fire.*

*H314 Causes severe skin burns and eye damage.*

*H335 May cause respiratory irritation.*

· **Precautionary statements**

*P101 If medical advice is needed, have product container or label at hand.*

*P102 Keep out of reach of children.*

*P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*

*P220 Keep apart from dirt, rust, chemicals, especially reducing substances, acids, alkaline solutions, amines and heavy metal compounds (such as accelerator, dessicative, metal soaps).*

*P234 Keep only in original container.*

*P271 Use only outdoors or in a well-ventilated area.*

*P280 Wear protective gloves/protective clothing/eye protection/face protection.*

*P301+P330+P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.*

*P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*

*P310 Immediately call a POISON CENTER/doctor.*

*P403+P235 Store in a well-ventilated place. Keep cool.*

*P405 Store locked up.*

*P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **2.3 Other hazards**

*Risk of serious damage to eyes.*

*Risk of fire on contact with combustible substances or other substances effective in promoting the decomposition reaction.*

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**Trade name: CHP-HÄRTER**

(Contd. of page 2)

- Fire propagating effect due to oxygen release.  
Thermal decomposition with temperatures above 50 °C (SADT)  
Pls. refer to section 10
- **Results of PBT and vPvB assessment**
  - **PBT:** Not applicable.
  - **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 123-42-2 EINECS: 204-626-7 Reg.nr.: 01-2119473975-21	4-hydroxy-4-methylpentan-2-one ⚠ Flam. Liq. 3, H226; ⚠ Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 131-11-3 EINECS: 205-011-6 Reg.nr.: 01-2119437229-36	dimethyl phthalate substance with a Community workplace exposure limit	25-50%
CAS: 12262-58-7 EINECS: 235-527-7	cyclohexanone, peroxide ⚠ Org. Perox. A, H240; ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; STOT SE 3, H335	20-<25%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.  
Personal protection for the First Aider.  
Take affected persons out of danger area and lay down.  
In case of irregular breathing or respiratory arrest provide artificial respiration.  
Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air or oxygen; call for doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
Call a doctor immediately.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. Then consult a doctor.  
Call a doctor immediately.
- **After swallowing:**  
IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
Call a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**Trade name: CHP-HÄRTER**

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.  
In case of fire, the product promotes combustion.  
May decompose explosively in absence of fire due to formation of vapour-air-mixture.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Do not inhale explosion gases or combustion gases.  
Wear self-contained respiratory protective device.  
Wear fully protective suit.
- **Additional information**  
Remove undamaged containers from the danger zone.  
Cool endangered receptacles with water spray.  
Collect contaminated fire fighting water separately. It must not enter the sewage system.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Use suitable respiratory protective device in case of insufficient ventilation.  
Avoid contact with the eyes and skin.  
Keep away from ignition sources.  
Pls. refer to section 10
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Collect with an inert, non-combustible, absorbent material (i.e. sand, diatomaceous earth, acid binder, universal binder).  
Do not seal receptacle gas tight.  
Dispose contaminated material as waste according to item 13.  
Pls. refer to section 10
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

GB

(Contd. on page 5)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**Trade name: CHP-HÄRTER**

(Contd. of page 4)

**SECTION 7: Handling and storage****· 7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Open and handle receptacle with care.

Do not return unused material to original containers – decomposition hazard!

Restrict the quantity stored at the work place.

Resistant to inert materials only.

Suitable materials: Stainless steel (DIN 1.4571), PVC, polyethylene, glass-lined apparatus.

Keep apart from dirt, rust, chemicals, especially reducing substances, acids, alkaline solutions, amines and heavy metal compounds (such as accelerator, desiccative, metal soaps). Avoid naked flames, sparks, other ignition sources and sunlight.

Avoid any direct contact with accelerators.

Weigh out and mix separately when processing polyester resins.

Avoid storage in containers with an airtight closure to prevent hazardous pressure build-up due to an eventual decomposition.

Avoid contact with the eyes and skin.

Ensure good ventilation/exhaustion at the workplace.

Do not inhale gases / fumes / aerosols.

Adhere to the workplace limit values and / or other threshold values.

**· Information about fire - and explosion protection:**

Protect from heat.

Keep ignition sources away - Do not smoke.

Prevent impact and friction.

Thermal decomposition with temperatures above 50 °C under formation of explosive vapours/gases

Avoid naked flames, sparks, other ignition sources and sunlight.

Protect against electrostatic charges.

Ground/bond container and receiving equipment.

Use explosion-proof apparatus / fittings and spark-proof tools.

Anti-explosion protection required

Fumes can combine with air to form an explosive mixture.

Fire propagating effect due to oxygen release.

Keep apart from incompatible substances, dirt and high temperatures.

Pls. refer to section 10

**· 7.2 Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Store only in the original receptacle.

Prevent any seepage into the ground.

Adhere to the provisions of the Law on Water Protection.

Use only receptacles specifically permitted for this substance/product.

**· Information about storage in one common storage facility:**

Keep apart from other chemicals, in particular from accelerators.

Store away from foodstuffs.

**· Further information about storage conditions:**

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Protect from contamination.

Store receptacle in a well ventilated area.

Store under lock and key and out of the reach of children.

**· Recommended storage temperature: < 25 °C**

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**Trade name: CHP-HÄRTER**

(Contd. of page 5)

· 7.3 *Specific end use(s)* No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

· *Additional information about design of technical facilities:* No further data; see item 7.

· 8.1 *Control parameters*

· *Ingredients with limit values that require monitoring at the workplace:*

**123-42-2 4-hydroxy-4-methylpentan-2-one**

WEL (Great Britain)	Short-term value: 362 mg/m <sup>3</sup> , 75 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm
---------------------	---

**131-11-3 dimethyl phthalate**

WEL (Great Britain)	Short-term value: 10 mg/m <sup>3</sup> Long-term value: 5 mg/m <sup>3</sup>
---------------------	--

· *DNELs*

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	Long-term exposure - systemic effects	3.4 mg/kg bw/day (general population)
Dermal	Long-term exposure - systemic effects	3.4 mg/kg bw/day (general population) 9.4 mg/kg bw/day (worker)
Inhalative	Long-term exposure - systemic effects	11.8 mg/m <sup>3</sup> (general population) 66.4 mg/m <sup>3</sup> (worker)
	Acute/short-term exposure - local effects	120 mg/m <sup>3</sup> (general population) 240 mg/m <sup>3</sup> (worker)
	Long-term exposure - local effects	11.8 mg/m <sup>3</sup> (general population) 66.4 mg/m <sup>3</sup> (worker)

· *PNECs*

**123-42-2 4-hydroxy-4-methylpentan-2-one**

PNEC aqua	2 mg/l (freshwater)
	0.2 mg/l (marine water)
PNEC sediment	9.06 mg/kg (freshwater)
	0.91 mg/kg (marine water)
PNEC STP	82 mg/l
PNEC soil	0.63 mg/kg (soil dw)

· *Additional information:* The lists valid during the making were used as basis.

· 8.2 *Exposure controls*

· *Personal protective equipment:*

· *General protective and hygienic measures:*

- Keep away from foodstuffs, beverages and feed.
- Do not eat, drink, smoke or sniff while working.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Immediately remove all soiled and contaminated clothing
- Take off contaminated clothing.
- Avoid contact with the eyes and skin.
- After contact with skin, wash immediately with plenty of soap and water.

(Contd. on page 7)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**Trade name: CHP-HÄRTER**

(Contd. of page 6)

Use skin protection cream for skin protection.

· **Respiratory protection:**

Ensure good ventilation/exhaustion at the workplace.

Adhere to the workplace limit values and / or other threshold values.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

DIN EN 374

Butyl rubber, BR

Chloroprene rubber, CR

Recommended thickness of the material:  $\geq 0.5$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

Value for the permeation: Level  $\leq 6$  ( $\geq 480$  min)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Fluid
Colour:	Colourless
Odour:	Light

· **pH-value:** Acidic

· **Change in condition**

Melting point/freezing point:	- 10 °C
Initial boiling point and boiling range:	Not applicable

· **Flash point:**  $>50$  °C

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**Trade name: CHP-HÄRTER**

(Contd. of page 7)

· <b>Ignition temperature:</b>	Not applicable
· <b>Auto-ignition temperature:</b>	Pls. refer to section 10
· <b>Explosive properties:</b>	Pls. refer to section 10
· <b>Density at 20 °C:</b>	~ 1.1 g/cm <sup>3</sup>
· <b>Solubility in / Miscibility with water:</b>	Partly miscible.
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C:</b>	~ 15 mPas
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No decomposition if used and stored according to specifications.
- **10.2 Chemical stability**  
Resistant to inert materials only.  
Suitable materials: Stainless steel (DIN 1.4571), PVC, polyethylene, glass-lined apparatus.
- **10.3 Possibility of hazardous reactions**  
Thermal decomposition or direct contact with numerous additives, such as reducing agents (i.e. amine accelerator), heavy metal compounds (in particular cobalt accelerators), acids and alkaline solutions, may lead to hazardous, autoaccelerating decomposition reactions, and possibly, to explosion or fire.
- **10.4 Conditions to avoid**  
Avoid naked flames, sparks, other ignition sources and sunlight.  
Protect from heat.  
>25 °C  
To avoid thermal decomposition do not overheat.  
Thermal decomposition with temperatures above 50 °C (SADT)
- **10.5 Incompatible materials:**  
Reacts with acids, alkalis and oxidising agents.  
Keep apart from dirt, rust, chemicals, especially reducing substances, acids, alkaline solutions, amines and heavy metal compounds such as accelerator, desiccative, metal soaps)  
Avoid any direct contact with accelerators.
- **10.6 Hazardous decomposition products:**  
Formation of various organic degradation products and inflammable and explosive vapours/gases upon decomposition.  
Danger of forming toxic pyrolysis products.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	LD50	3002 mg/kg (rat) (OECD 401)
Dermal	LD50	13630 mg/kg (rab)
	LD 50	> 1875 mg/kg (rat) (OECD 402)

(Contd. on page 9)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**Trade name: CHP-HÄRTER**

(Contd. of page 8)

Inhalative	LC 50 / 4h	> 7.6 mg/l (rat) (OECD 403)
	LC50 /4h	500-1900 mg/m <sup>3</sup> (mouse)

**12262-58-7 cyclohexanone, peroxide**

Oral	LD50	880 mg/kg (mouse)
Dermal	LD 50	> 2000 mg/kg
Inhalative	LC 50 / 4h	> 5.0 mg/l (rat)
	LC0 /4h	5.0 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**  
Causes serious eye damage.

· **Subacute to chronic toxicity:****123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	NOAEL	300 mg/kg (rat) (6 weeks, liver, kidney)
Inhalative	NOAEL	1.041 mg/l (rat) (6 weeks, liver, kidney)
	LOAEL	0.48 mg/l (human)

- **Additional toxicological information:**  
Has a narcotising effect.  
Irritating to respiratory system.
- **Sensitisation** No sensitising effects known.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

· **Carcinogenicity****123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	NOAEL (carcinogenicity)	100 mg/kg (rat) (44 d)
Inhalative	NOAEL (carcinogenicity)	1.84 mg/l (rat)

· **Reproductive toxicity/Fertility****123-42-2 4-hydroxy-4-methylpentan-2-one**

Oral	NOAEL (fertility)	30-100 mg/kg (rat, parents) (OECD 422)
		300 mg/kg (rat, F1) (OECD 422)
Inhalative	NOAEL (fertility)	4.1 mg/l (rat, parents) (OECD 416)
		4.1 mg/l (rat, F1) (OECD 416)

· **Reproductive toxicity/Teratogenicity****123-42-2 4-hydroxy-4-methylpentan-2-one**

Inhalative	NOAEL (teratogenicity)	4.1 mg/l (rat) (OECD 414)
------------	------------------------	---------------------------

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

GB

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

Trade name: **CHP-HÄRTER**

(Contd. of page 9)

## SECTION 12: Ecological information

### · 12.1 Toxicity

#### · Aquatic toxicity:

##### **123-42-2 4-hydroxy-4-methylpentan-2-one**

EC50	9016 mg/l (daphnia) (24h, OECD 203)
EC50/48h	> 1000 mg/l (daphnia magna) (OECD 202)
EC50/72h	> 100 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50/0.5h	17 mg/l (activated slugde)
LC50/96h	420 mg/l (Lepomis macrochirus)
	> 100 mg/l (Oryzias latipes) (OECD 203)
NOEC	100 mg/l (Pseudokirchneriella subcapitata) (OECD 201, 72h)
NOEC (aqua chron.)	> 100 mg/l (daphnia magna) (21 d)
NOEL	825 mg/l (pseudomonas putida)
TGK = toxicity threshold concentration	825 mg/l (pseudomonas putida) (16h, inhibition test)

##### **12262-58-7 cyclohexanone, peroxide**

EC50/0.5h	11.1 mg/l (activated slugde)
LC50/96h	48 mg/l (danio rerio)
	48 mg/l (piscis)

### · 12.2 Persistence and degradability

biodegradable

##### **123-42-2 4-hydroxy-4-methylpentan-2-one**

Biodegradation 98.51 % (OECD 301A, 28d)

### · 12.3 Bioaccumulative potential

##### **123-42-2 4-hydroxy-4-methylpentan-2-one**

log Kow	-0.09
BCF	0.5

##### **12262-58-7 cyclohexanone, peroxide**

log Kow 3.02 (calculated)

### · Behaviour in environmental systems:

#### · 12.4 Mobility in soil

##### **123-42-2 4-hydroxy-4-methylpentan-2-one**

log Koc	0.52
Koc	3.32

### · Additional ecological information:

#### · General notes:

Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

#### · 12.5 Results of PBT and vPvB assessment

· **PBT:** Not applicable.· **vPvB:** Not applicable.

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

Trade name: **CHP-HÄRTER**

(Contd. of page 10)

· **12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.  
Disposal must be made according to official regulations.

Dilute product with suitable inert liquid to a peroxide concentration below 10% and subsequently dispose of according to the refuse disposal act.

· **Waste disposal key:**

The waste codes given above are to be considered recommendations; because of regional and industrial sector specific features, application of different waste codes is possible.

· **European waste catalogue**

16 05 06*	laboratory chemicals, consisting of or containing dangerous substances, including mixtures of laboratory chemicals
-----------	--

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN3105

· **14.2 UN proper shipping name**

· **ADR** 3105 ORGANIC PEROXIDE TYPE D, LIQUID  
· **IMDG, IATA** ORGANIC PEROXIDE TYPE D, LIQUID

· **14.3 Transport hazard class(es)**

· **ADR, IMDG, IATA**



· **Class** 5.2 Organic peroxides.

· **Label** 5.2

· **14.4 Packing group**

· **ADR, IMDG, IATA** Void

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Organic peroxides.

· **EMS Number:** F-J,S-R

· **Stowage Category** D

· **Stowage Code** SW1 Protected from sources of heat.

(Contd. on page 12)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**Trade name: CHP-HÄRTER**

(Contd. of page 11)

- |  |   |
|--|---|
| · <b>Segregation Code</b>  | SG35 Stow "separated from" acids.<br>SG36 Stow "separated from" alkalis.<br>SG72 See 7.2.6.3.2. |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b> | Not applicable.   |
| · <b>Transport/Additional information:</b>                                       |   |
| · <b>ADR</b>   |   |
| · <b>Limited quantities (LQ)</b>   | 125 ml  |
| · <b>Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity  |
| · <b>Tunnel restriction code</b>   | D   |
| -----  |   |
| · <b>IMDG</b>  |   |
| · <b>Limited quantities (LQ)</b>   | 125 ml  |
| · <b>Excepted quantities (EQ)</b>  | Code: E0<br>Not permitted as Excepted Quantity  |

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Information about limitation of use:**  
Employment restrictions concerning juveniles must be observed.  
Employment restrictions concerning pregnant and lactating women must be observed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H226 Flammable liquid and vapour.  
H240 Heating may cause an explosion.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.
- **Department issuing SDS:** Abteilung Labor
- **Contact:** Frau S. Schaller
- **Abbreviations and acronyms:**  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 13)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 23.05.2017

V - 3

Revision: 23.05.2017

**Trade name: CHP-HÄRTER**

(Contd. of page 12)

*IATA: International Air Transport Association*  
*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*  
*EINECS: European Inventory of Existing Commercial Chemical Substances*  
*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*DNEL: Derived No-Effect Level (REACH)*  
*PNEC: Predicted No-Effect Concentration (REACH)*  
*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*Flam. Liq. 3: Flammable liquids – Category 3*  
*Org. Perox. A: Organic peroxides – Type A*  
*Org. Perox. D: Organic peroxides – Type C/D*  
*Acute Tox. 4: Acute toxicity – Category 4*  
*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*  
*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*  
*Eye Irrit. 2: Serious eye damage/eye irritation – Category 2*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

**\* Data compared to the previous version altered.**

GB